

Pokini **A**

Small. Robust. Fanless.



Available until 2020

Hard soldered AMD CPU

Low power consumption

Several front interfaces (optional)

passive cooling



fanless



certified dust protection



temperature range: -40°F up to 158°F



optional VESA/ DIN-Rail mounting



Use two displays at a time

OS	Microsoft Windows XP / 7 / 8 (x32/x64) Linux (Suse / Ubuntu / Redhat)
CPU	AMD® G-T40E (2x 1,00 GHz) AMD® G-T56N (2x 1,65 GHz)
RAM	2x SO-DIMM DDR3 PC1333, max. 16 GB
Storage	1x 2,5", 1x mSATA
Graphics	G-T40E: AMD Radeon HD 6250 G-T56N:....AMD Radeon HD 6320
Display Interface 1	HDMI 1.4a (1920 x 1200 @ 60Hz)
Display Interface 2	DisplayPort 1.1a (2560 x 1600 @ 60Hz)
Audio	Realtek ALC888-VC2 - 7.1 HD Audio
LAN	1x RJ45 @ 10/100/1000 Mbit/s (Realtek RTL8111F-CG)
Wireless	WLAN 802.11b/g/n, Bluetooth 3.0
Rear interfaces	2x USB 3.0, 2x USB 2.0 2x eSATA 1x HDMI, 1x DisplayPort 1x LAN Mic-In, Audio-Out 1x mini serial (RS-232 with DB9 adapter) 2x WLAN antenna DC-In

Front interfaces	Depending on Front module (Please ask for information)
Internal interfaces	1x Micro SIM Slot (6 Pins)
Special features	Auto-Power-On, Wake-on-LAN, Wake-on-Timer, PXE-Boot, Watchdog
Power supply	Power-input: 10-15V Consumption: 7W - 24W
Measurements	190mm x 40mm x 160mm, approx. 1300g
MTBF	> 100.000 hours
Warranty	2 years bring-in warranty (up to 5 years)