

Pokini

Robust. Fanless. Powerful.



Available until 2020

Hard soldered CPU

Smart and powersaving

Front-extendion-modules available

4th Generation Intel® CPU



fanless



certified dust protection



temperature range: -40°F up to 158°F



available VESA/ DIN-Railmount



Use 3 displays at a time

OS	Microsoft Windows 7 / 8.1 Professional Microsoft Windows 10 Professional / IoT Linux (Suse / Ubuntu / Redhat)
CPU	Intel® Core™ i3-4010U (2x 1,70 GHz) Intel® Core™ i5-4300U (2x 1,90 GHz up to 2,90 GHz with Intel® Turbo-Boost) Intel® Core™ i7-4600U (2x 2,10 GHz up to 3,30 GHz with Intel® Turbo-Boost)
RAM	2x SO-DIMM DDR3 PC1600, max. 16 GB
Storage	1x 2,5", 1x mSATA
Graphics	Intel® HD4400
Display Interface 1	HDMI 1.4 (4096 x 2304 @ 24Hz)
Display Interface 2	DisplayPort 1.2 (3200 x 2000 @ 60Hz)
Display Interface 3	HDMI 1.4 (4096 x 2304 @ 24Hz)
Audio	Realtek ALC888 - 7.1 HD Audio
LAN	2x RJ45 @ 10/100/1000 Mbit/s (1x Intel® I218 + 1x Intel® I211)
Wireless	WLAN 802.11ac (Intel® 7260HMW) Bluetooth 4.0

Rear interfaces	2x USB 3.0, 2x USB 2.0 2x HDMI, 1x DisplayPort, 2x LAN Mic-In, Audio-Out 3x mini serial (2x Full RS-232, 1x 2-wire) Power-Button, DC-In 2x WLAN antenna
Front interfaces	2x USB 3.0, Please ask for other extentions
Internal interfaces	1x Micro SIM Slot (6 Pins)
Special features	Intel® vPro (i5 and i7), Auto-Power-On, Wake-on-LAN, PXE-Boot
Power supply	Power-input: 10-15V Consumption: 6W - 24W
Measurements	190mm x 35mm x 160mm, approx. 1200g
Warranty	2 years bring-in warranty (up to 5 years)