

# Pokini

Small. Robust. Fanless.



Available until 2020

CPU and RAM hard soldered

Low power consumption

Made for 24/7 use

Passive cooling



fanless



certified dust protection



temperature range: -40°F bis 185°F



Optionale VESA/ DIN-Rail mount

OS

Microsoft Windows XP / 7 (x32)

Linux Mint 13 MATE

CPU

Intel® Atom Z530  
(1x 1,60 GHz)

RAM

2 GB DDR2-533 (hard soldered)

Storage

1x 2,5"

Graphics

Intel® GMA500

Display Interface 1

DVI via HDMI Port (1600 x 1200 @ 60Hz)

Audio

Realtek ALC662-VC-GR - 5.1 HD Audio

LAN

2x RJ45 @ 10/100/1000 Mbit/s  
(Realtek RTL8111F-CG)

Wireless

WLAN 802.11b/g/n

Rear interfaces

2x USB 2.0  
1x HDMI (only video)  
2x LAN  
S/PDIF, Mic-In,  
1x WLAN antenna  
Reset-Button  
DC-In

Front interfaces

2x miniUSB 2.0  
1x RS-232 (mini-serial with DB-9 Connector)  
1x microSD-Card Slot (SD, SDHC, SDXC)  
Power-Button

Special features

Auto-Power-On, Wake-on-LAN, PXE-Boot

Power supply

Power input: 10-15V  
Consumption: 4,5W - 9W

Measurements

115mm x 27mm x 101mm, approx. 350g

MTBF

> 100.000 hours

Warranty

2 years bring-in warranty

