

Pokini

Small. Powerful. Flexible.



Available until 2026

Casted aluminum case

For 24x7 use

Optional WLAN//4xLAN



fanless



certified dust protection



temperature range: -40°F up to 158°F



optional VESA/DIN-Rail mount

OS

Microsoft Windows 7 / 8.1 Professional
Microsoft Windows 10 Professional / IoT
Linux (Suse / Ubuntu / Redhat)

CPU

AMD® A10 Micro-6700T
(4x 1,20 GHz up to 2,20 GHz)

RAM

1x SO-DIMM DDR3 PC1333, max. 8 GB

Storage

1x mSATA

Graphics

AMD® Radeon R6

Display Interface 1

HDMI 1.4a (1920 x 1200 @ 60Hz)

Display Interface 2

HDMI 1.4a (1920 x 1200 @ 60Hz)

Audio

Realtek ALC886 - 7.1 HD Audio

LAN

1x RJ45 @ 10/100/1000 Mbit/s
(Intel® I211)

Rear interfaces

1x USB 3.0
1x USB 2.0
2x HDMI
1x LAN
1x mini-serial RS232 (with DB9 adaptor)
1x 8-Bit GPIO
DC-In

Front interfaces

1x USB 3.0
2x USB 2.0
Line-Out, Line-In
microSD-Card slot
Power-Button

Internal interfaces

1x microSIM (6 Pins)

Available extension-kits:

Pokini F C67 Entry

Without any extensions

Pokini F C67 WLAN

WLAN 802.11ac (2.4/5GHz Intel 7260HMW)
Bluetooth 4.0
1x eSATA (powered)
1x additional GbE LAN (dedicated Intel® I211)

Pokini F C67 4LAN

3x additional GbE LAN (dedicated Intel® I211)

Special features

Auto-Power-On, Wake-on-LAN, Wake-on-Timer, PXE-Boot, Watchdog

Power supply

Power-input: 10-15V
Consumption: 4,5W - 10,5W

Measurements

108mm x 24mm x 83mm, approx. 400g

Warranty

5 years bring-in warranty