

Pokini

Small. Robust. Fanless.



Available until 2020

CPU and RAM hard soldered

Low power consumption

Made for 24/7 use

Passive cooling



fanless



certified dust protection



temperature range: -40°F bis 185°F



Optionale VESA/ DIN-Rail mount

OS	Microsoft Windows XP / 7 (x32) Linux Mint 13 MATE
CPU	Intel® Atom Z530 (1x 1,60 GHz)
RAM	2 GB DDR2-533 (hard soldered)
Storage	1x 2,5"
Graphics	Intel® GMA500
Display Interface 1	DVI via HDMI Port (1600 x 1200 @ 60Hz)
Audio	Realtek ALC662-VC-GR - 5.1 HD Audio
LAN	2x RJ45 @ 10/100/1000 Mbit/s (Realtek RTL8111F-CG)
Wireless	WLAN 802.11b/g/n

Rear interfaces

2x USB 2.0
1x HDMI (only video)
2x LAN
S/PDIF, Mic-In,
1x WLAN antenna
Reset-Button
DC-In

Front interfaces

2x miniUSB 2.0
1x RS-232 (mini-serial with DB-9 Connector)
1x microSD-Card Slot (SD, SDHC, SDXC)
Power-Button

Special features

Auto-Power-On, Wake-on-LAN, PXE-Boot

Power supply

Power input: 10-15V
Consumption: 4,5W - 9W

Measurements

115mm x 27mm x 101mm, approx. 350g

MTBF

> 100.000 hours

Warranty

2 years bring-in warranty

